

WIRE FEEDER

SKY 4S - WLF 4S



			SKY 4S	WLF 4S
Codice	Code	Standard	SKY000002	WLF000002
Alimentazione	Input primary	V ac	42/24	42/24
Regolazione filo	Wire speed control	m/min.	0,2-23	0,2-23
Selettore	Time selector		2/4 T	2/4T
Pulsante avanzamento filo	Wire inching		di serie/standard	di serie/standard
Pulsante prova gas	Gas test		di serie/standard	di serie/standard
Copribobina in ABS	ABS coil cover	15 Kg	di serie/standard	-
Dimensioni	Dimensions	L mm	700	660
		W mm	245	240
		H mm	400	450
Peso	Weight	Kg	14	18

Caratteristiche tecniche e accessori - Technical details and accessories



Traino 4 rulli in alluminio
Aluminium Feed plate 4 rolls



Copribobina ø 300mm
Coil Cover ø 300mm

SKY 4S - WLF 4S

WIRE FEEDER



La Serie Sky 4S/WLF 4S è stata realizzata per essere applicata ai generatori con la regolazione a scatti della tensione di saldatura, come i nostri BLUE ONE. Si presentano completi di: regolazione velocità filo, kit 2/4 tempi, prova gas, prova filo; a richiesta kit digitale V+A, flussimetro e tachimetrica. Il filo è spinto da un sistema trainante a 4 rulli.

The Sky 4S/WLF 4S Series it has been designed to be applied to generators with step regulation of the welding voltage, like ours BLUE ONE. The unit is supplied complete with: wire speed control, 2/4 cycles kit, gas test, wire test; on request digital meter V+A, flowmeter kit and tachometer. The wire is drive by a feeding system with 4 rollers.